

# Alfa Laval TL15

# Gasketed plate heat exchanger for a wide range of applications

#### Introduction

Alfa Laval Industrial line is a wide product range that is used in virtually all types of industry.

The relatively tall plate makes this model suitable for duties with long temperature programs and when high heat recovery is appreciated. A large range of plate and gasket types is available.

# **Applications**

- · Biotech and Pharmaceutical
- Chemicals
- Energy and Utilities
- Food and Beverages
- Home and Personal care
- HVAC and Refrigeration
- · Machinery and Manufacturing
- Marine and Transportation
- Mining, Minerals and Pigments
- Pulp and Paper
- Semiconductor and Electronics
- Steel
- Water and Waste treatment

# Benefits

- High energy efficiency low operating cost
- Flexible configuration heat transfer area can be modified
- Easy to install compact design
- High serviceability easy to open for inspection and cleaning and easy to clean by CIP
- Access to Alfa Laval's global service network

#### **Features**

Every detail is carefully designed to ensure optimal performance, maximum uptime and easy maintenance. Selection of available features, depending on configuration some features may not be applicable:







- Five-point alignment
- Corner guided alignment system
- Chocolate pattern distribution area
- Clip-ad gasket
- · Offset gasket groove
- Leak chamber



- Bearing boxes
- Fixed bolt head
- Key hole bolt opening
- Lifting lug
- Lining
- · Lock washer
- Pressure plate roller
- Tightening bolt cover

## Alfa Laval 360° Service Portfolio

Our extensive service offering ensure top performance from your Alfa Laval equipment throughout its life cycle. The Alfa Laval 360 Service Portfolio include installation services, cleaning and repair as well as spare parts, technical documentation and trouble shooting. We also offer replacement, retrofit, monitoring and much more.


For information about our complete service offering and how to contact us - please visit www.alfalaval.com/service.


#### General remarks for technical information

- The global offering presented in this leaflet may not be available for all regions
- All combinations may not be configurable

### **Dimensional drawing**

Measurements mm (inches)





Туре	Н	W	h
TL15-FM	2752 (108.3")	610 (24.0")	342 (13.5")
TL15-FG	2752 (108.3")	637 (25.1")	342 (13.5")
TL15-FG, ASME	2752 (108.3")	646 (25.4")	342 (13.5")
TL15-FD, ASME	2752 (108.3")	646 (25.4")	342 (13.5")
TL15-FG	2752 (108.3")	646 (25.4")	342 (13.5")
TL15-FS, ASME	2752 (108.3")	646 (25.4")	342 (13.5")

### Technical data

Plates	туре	Free channel, mm (inches)	
TL15-B	Single plate	1.9 (0.075)	
Materials			
Heat transfer plates		304/304L, 316/316L	
		Ti	
Field gask	ets	NBR, EPDM	
		Carbon steel	
Flange connections		Metal lined: stainless steel, titanium	
		Rubber lined: NBR, EPDM	
Frame and pressure plate		Carbon steel, epoxy painted	

Other materials may be available on request

# Operational data

Frame, PV-code	Max. design pressure (barg/psig)	Max. design temperature (°C/°F)
FM, pvcALS	10.0/145	180/356
FG, pvcALS	20.0/290	200/392

Frame, PV-code	Max. design pressure (barg/psig)	Max. design temperature (°C/°F)
FG, ASME	10.3/150	250/482
FG, PED	20.0/290	200/392
FD, ASME	20.7/300	250/482
FS, pvcALS	35.0/507	200/392
FS, ASME	31.7/460	250/482
FS, PED	35.0/507	200/392

Extended pressure and temperature rating may be available on request.

#### Flange connections

EN 1092-1 DN150 PN10 FM, pvcALS  ASME B16.5 Class 150 I  JIS B2220 10K 150A  EN 1092-1 DN150 PN16  EN 1092-1 DN150 PN26  FG, pvcALS  ASME B16.5 Class 150 I  JIS B2220 10K 150A  JIS B2220 16K 150A  FG, ASME  ASME B16.5 Class150 N	NPS 6
JIS B2220 10K 150A EN 1092-1 DN150 PN16 EN 1092-1 DN150 PN26 FG, pvcALS ASME B16.5 Class 150 I JIS B2220 10K 150A JIS B2220 16K 150A FG, ASME ASME B16.5 Class150 N	3
EN 1092-1 DN150 PN16 EN 1092-1 DN150 PN26 EN 1092-1 DN150 PN26 FG, pvcALS ASME B16.5 Class 150 I JIS B2220 10K 150A JIS B2220 16K 150A FG, ASME ASME B16.5 Class150 N	5
EN 1092-1 DN150 PN25 FG, pvcALS  ASME B16.5 Class 150 I  JIS B2220 10K 150A  JIS B2220 16K 150A  FG, ASME  ASME B16.5 Class150 N	5
FG, pvcALS  ASME B16.5 Class 150 I  JIS B2220 10K 150A  JIS B2220 16K 150A  FG, ASME  ASME B16.5 Class150 N	•
JIS B2220 10K 150A JIS B2220 16K 150A FG, ASME ASME B16.5 Class150 N	NIDS 6
JIS B2220 16K 150A FG, ASME ASME B16.5 Class150 N	INF O U
FG, ASME ASME B16.5 Class150 N	
	NPS 6
EN 1092-1 DN150 PN16	3
FG, PED EN 1092-1 DN150 PN25	5
ASME B16.5 Class 150 I	NPS 6
FD, ASME ASME B16.5 Class 300 I	NPS 6
FDc, ASME	
EN 1092-1 DN150 PN25	5
EN 1092-1 DN150 PN40	)
FS, pvcALS ASME B16.5 Class 400 I	NPS 6
JIS B2220 10K 150A	
JIS B2220 20K 150A	
FS, ASME ASME B16.5 Class 400 I	NPS 6
EN 1092-1 DN150 PN25	
FS, PED EN 1092-1 DN150 PN40	,
ASME B16.5 Class 400 I	•

Standard EN1092-1 corresponds to GOST 12815-80 and GB/T 9115.

This document and its contents are subject to copyrights and other intellectual property rights owned by Alfa Laval Corporate AB. No part of this document may be copied, re-produced or transmitted in any form or by any means, or for any purpose, without Alfa Laval Corporate AB's prior express written permission. Information and services provided in this document are made as a benefit and service to the user, and no representations or warranties are made about the accuracy or suitability of this information and these services for any purpose. All rights are reserved.

CHE00085-4-EN-GB © Alfa Laval Corporate AB